







Shenzhen yulian technology co., LTD

PCT-10系列 Series

技术参数 Technical parameter

 <p>PCT-102</p>	
 <p>PCT-104</p>	
 <p>PCT-106</p>	
 <p>PCT-108</p>	

型号 Model	PCT-102	PCT-104	PCT-106	PCT-108
外形尺寸 Appearance Specification				
参考标准 Reference standard	IEC	IEC	IEC	IEC
额定电压 Rated voltage	250V	250V	250V	250V
额定电流 Rated current	24A	24A	24A	24A
导线线径 Wire diameter	0.5-2.5mm ²	0.5-4mm ²	0.5-2.5mm ²	0.5-2.5mm ²
耐电压 Voltage resistance	4kV	4kV	4kV	4kV
机械性能 Mechanical properties				
环境温度 Ambient temperature	-40°C~+105°C	-40°C~+105°C	-40°C~+105°C	-40°C~+105°C
剥线长度 Strip length	10-12mm	10-12mm	10-12mm	10-12mm
长×宽×高 L/W/H	19.6×9.1×12.9	19.4×13×13.4	19.4×18.6×13.4	19.4×24.2×13.4
极数 The number of poles	2P	4P	6P	8P
盖子颜色 Lid colour	●	●	●	●
塑件 Plastic parts	PC,UL94,V-2	PC,UL94,V-2	PC,UL94,V-2	PC,UL94,V-2
弹片 Shrapnel	S301	S301	S301	S301
触点材料 Conductor material	T2	T2	T2	T2




第一步 First Step
按标定长度剥去导线外皮。
strip the wire 10-12mm



第二步 Second Step
将剥去外皮的导线完全插入连接器即可。
Plug the wire completely into the connector.

0.5~2.5mm²
250V/4kV/24A



接线图示意

