



Shenzhen yulian technology co., LTD

接线帽系列 Series



技术参数 Technical parameter

型号 Model	P1	P2	P3	P4	P6
参考标准 Reference standard	IEC	IEC	IEC	IEC	IEC
额定电压 Rated voltage	450V	450V	450V	450V	450V
额定电流 Rated current	24A	24A	24A	24A	24A
导线线径 Wire diameter	0.2-2.5mm ²	0.5-2.5mm ²	0.5-4mm ²	0.5-6mm ²	0.5-10mm ²
耐电压 Voltage resistance	4kV	4kV	4kV	4kV	4kV
机械性能 Mechanical properties					
环境温度 Ambient temperature	-40°C~+105°C	-40°C~+105°C	-40°C~+105°C	-40°C~+105°C	-40°C~+105°C
剥线长度 Strip length					
长×宽×高 L/W/H	Ø8.3×14.9	Ø9.5×17.2	Ø12.9×21.9	Ø14×23.8	Ø16×26.6
极数 The number of poles	1P	1P	1P	1P	1P
盖子颜色 Lid colour	●	●	●	●	●
塑件 Plastic parts	PP	PP	PP	PP	PP
弹片 Shrapnel					
触点材料 Conductor material	T2	T2	T2	T2	T2

Shenzhen yulian technology co., LTD

ADD: 1F, J Bui l di ng, shi feng
technology park, Loucun guangmi ng
shenzhen.

Tel & wechat & whatsapp: +8618028767259

Email: lisa@sz-yulian.com

Web: <https://szyul.en.alibaba.com>

